

UTM MSDS, 01-3047 Target Bullet Rounds
Revision No. 2

Revision Date: April 2018
Supersedes: January 2017

This SDS has been prepared to GHS formatting, but is not a mandated SDS and provided for information purposes only.

SECTION 1.

Product and Company Identification

UK & ROW Supplier:

UTM Ltd.
Hampstead Avenue
Mildenhall
Suffolk IP28 7AS
United Kingdom
www.utmworldwide.com

USA Supplier:

UTM Inc.
55 Readington Rd.
North Branch, NJ 08876
USA

Customer Service:

United Kingdom & ROW: +44 (0) 1638 711 003
Unites States Sales Office: 1-877-866-7233
United States Headquarters: 908-725-9000

Product Name:

Cartridges, Small Arms, Target Bullet Rounds. (Non – Lethal Training Ammunition).

Synonyms: Target Bullet Rounds, TBR.

Types: 5.56mm.

Technical Support Service:

United Kingdom & Rest of World (ROW): sales@utmworldwide.com
Unites States: us.sales@utmworldwide.com, us.military.sales@utmworldwide.com

Emergency Phone Number:

UK/ Rest of World (ROW): +44 (0)1638 711 003
USA: 1-877-866-7233 or 908-725-9000

Emergency Phone Hours:

UK/ Rest of World (ROW) : 9am to 5pm GMT
USA: 9am to 5pm EST

SECTION 2.

Hazards Identification

Appearance / Odours:

An odourless metallic cylindrical cartridge, having a metallic projectile covered with a red plastic dome.

Emergency Overview:

Warning!

Explosive, Keep away from heat.

Do not subject to mechanical shock.

Particles from firing may be harmful if inhaled.

Use (Training) without the appropriate Personal Protective equipment can cause bodily injury.

Do not take internally.

Continued on page 2

SECTION 2.

Hazards Identification (continued)

Specific Physical Hazards Arising From Product:

Packaged and Loose cartridges could function (cook-off) if exposed to an external heat source in excess of 135°C (275°F) and could produce low velocity fragments which could cause eye injury or superficial skin wounds.

Caution:

When UTM training ammunition is fired, small amounts of particles can be emitted as well as gases. Upon over exposure this can be slightly irritating to the eye and respiratory tract. Emitted particles and or gases may contain trace amounts of harmful substances.

OSHA Regulatory Status:

This product contains material (s) considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

This product contains potential carcinogens as listed by OSHA, IARC or NTP.

(Note: Potential carcinogens as listed by OSHA, IARC or NTP are contained within the spent cartridge case, and do not vent to atmosphere under normal firing or handling conditions.)

United Nations Hazard Classification:

Classification 1.4S

United Nations Designation:

UN0012

Potential Health Effects:

Notes: This product unused is composed of various components sealed inside a metallic cartridge. Normal handling of this product in this condition poses no threat of exposure from harmful materials.

It is unlikely that the concentration of particles one would be exposed to from normal firing of this product would be sufficient to cause any of the effects listed.

Lead: Ingestion of large amounts of Lead can cause abdominal pain, constipation, cramps, nausea and/or vomiting. Chronic exposure to Lead can cause kidney damage, anaemia, reproductive effects, developmental effects and permanent nervous system damage in humans including changes in cognitive function.

Barium Nitrate: Irritation to eyes, skin, upper respiratory system; skin burns; gastroenteritis; muscle spasm; slow pulse, extrasystoles; hypokalemia

Antimony (III) Sulphide: Harmful by inhalation and if swallowed. May be harmful in contact with the skin. Skin, eye and respiratory irritant. Chronic exposure may lead to kidney or liver damage.

Tetrazene: May be harmful if swallowed or inhaled. Skin and eye irritant.

Pentrite: Is a known coronary vasodilator and ingestion or inhalation may result in a lowering of blood pressure. Skin and eye irritant.

Glass Powder: May be harmful if swallowed or inhaled. Skin and eye irritant.

Nitrocellulose: Inhalation may irritate your nose, throat, skin and eyes. Toxic gases, such as oxides of nitrogen, hydrogen cyanide and carbon monoxide, which may be produced during decomposition or combustion of nitrocellulose.

Styphnic Acid: Harmful if swallowed, if in contact with skin and if inhaled.

Diphenylamine: Irritation to eyes, skin, mucous membrane; eczema; tachycardia, hypertension; cough, sneezing; methemoglobinemia; increased blood pressure, heart rate; proteinuria, hematuria (blood in the urine), bladder injury; In Animals: teratogenic effects.

Medical Conditions Aggravated by Exposure:

There are no medical conditions known to be aggravated by exposure to this product in its solid un-fired form.

Exposure to Lead can aggravate Anemia, Cardiovascular and Respiratory Disease.

Potential Environmental Effects:

No Data.

Lead has been shown to be toxic to aquatic species.

SECTION 3.

Components.

Product may contain the components listed below.

Component		Percentage by weight of cartridge	CAS #
CARTRIDGE CASE			
Aluminium Slide	Silicon	<1.0%	7440-21-3
	Iron	<0.4%	7439-89-6
	Copper	1.7%	7440-50-8
	Zinc	<1.0%	7440-66-6
	Lead	<0.2%	7439-92-1
	Bismuth	<0.5%	7440-69-9
	Aluminium	27.6%	7429-90-5
	Magnesium	<1.0%	7439-95-4
	Manganese	<0.5%	7439-96-5
	Chromium	<0.2%	7440-47-3
	Tin	<0.1%	7440-31-5
Steel Body	Titanium	<0.1%	7440-32-6
	Carbon	<0.1%	7440-44-0
	Iron	55.4%	7439-89-6
	Lead	<0.2%	7439-92-1
	Manganese	<1.0%	7439-96-5
	Sulfur	<0.2%	7704-34-9
	Silicon	<0.3%	7440-21-3
Primer Cups	Phosphorous	<0.1%	7723-14-0
	Copper	7.2%	7440-50-8
	Iron	<0.1%	7439-89-6
	Lead	<0.1%	7439-92-1
O Ring	Zinc	3.8%	7440-66-6
	Nitrile	<0.3%	Not Listed
Striker Ball	Polyamide 66	<1.0%	32131-17-2
	Glass Fibre	<0.3%	65997-17-3
PROJECTILE			
Projectile Body	Silicon	<0.1%	7440-21-3
	Iron	<0.1%	7439-89-6
	Copper	<0.3%	7440-50-8
	Zinc	<0.2%	7440-66-6
	Lead	<0.1%	7439-92-1
	Bismuth	<0.1%	7440-69-9
Dome	Aluminium	4.1%	7429-90-5
	Polyamide 66	<0.5%	32131-17-2
PRIMERS (FRONT)			
Primary Explosive	Lead Trinitroresorcinate	<0.2%	15245-44-0
	Barium Nitrate	<0.2%	10022-31-8
	Antimony (III) Sulphide	<0.1%	1345-04-6
	Tetrazene	<0.1%	109-27-3
	Lead Dioxide	<0.1%	1309-60-0
	Minium	<0.1%	1314-41-6
	Penthrite	<0.1%	78-11-5
PRIMERS (REAR)			
Primary Explosive	Lead Trinitroresorcinate	<0.2%	15245-44-0
	Barium Nitrate	<0.2%	10022-31-8
	Tetrazene	<0.1%	109-27-3
	Lead Dioxide	<0.1%	1309-60-0
	Minium	<0.1%	1314-41-6
	Glass Powder	<0.2%	65997-17-3
	Styphnic Acid	<0.1%	82-71-3
	Nitrocellulose	<0.1%	9004-70-0
	Diphenylamine	<0.1%	122-39-4
	Centralite I	<0.1%	85-98-3
	2,4-Dinitroanisole	<0.1%	119-27-7
Propellant	Nitrocellulose	<0.3%	9004-70-0
	Diphenylamine	<0.1%	122-39-4
	Centralite I	<0.1%	85-98-3
	Graphite Coating	<0.1%	7782-42-5
	2,4-Dinitroanisole	<0.1%	119-27-7

Percentage of non reduced hazard substance as a percentage of the weight of the finished assembled round is 0.97%.

SECTION 4.

First Aid Measures

*** Eye Contact:**

Immediately flush out fume or particles with large amounts of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If eye irritation develops, call a physician immediately.

***Skin Contact:**

Wash skin with plenty of soap and water.

***Inhalation:**

If symptoms of lung irritation occur (coughing, wheezing or breathing difficulty), remove from exposure area to fresh air immediately. If breathing has stopped, perform artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.

Ingestion:

If ingested, immediately call a physician.

Items marked with an asterisk (*) are conditions associated with the firing or discharge of the product and under normal conditions of transportation and handling of the product would not be a risk.

SECTION 5.

Fire Fighting Measures

Flammable Properties:

May detonate if heated to 135°C (275°F).

Suitable Extinguishing Media:

Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used.

Cool the containing vessel with a water jet in order to prevent the ammunition from functioning (cook-off).

Use water to cool ordinary surrounding combustibles.

Use flooding quantities of water.

Use wide fog pattern nozzle to stop any low velocity fragments.

Specific Hazards Arising From Product:

Packaged and Loose cartridges could function (cook-off) due to direct exposure to an external heat source and could produce low velocity metallic fragments which could cause eye injury or superficial skin wounds.

Protective Equipment & Precautions for Fire-fighters:

Wear full fire-fighter protective equipment including face shield or SCBA.

Minimum recommended distance for rescue personnel 10 meters (11 yards).

Evacuate the area to a radius of 100 meters (110 yards).

SECTION 6.

Accidental Release Measures

Methods for Containment:

Spills of this material should be handled carefully. Do not subject materials to mechanical shock. A spill of this material will normally not require emergency response team capabilities.

Methods for Clean-up:

If ammunition packing case should rupture, any loose cartridges should be placed into UTM classified packaging and the lid carefully secured.

Damaged/ Defective Ammunition should be quarantined into UTM classified packaging and disposed of in accordance with local instructions for defective ammunition, such as burnt in a standard ammunition incinerator.

SECTION 7.

Handling & Storage

Handling:

Keep out of reach of any unauthorized personnel.

Keep out of reach of children.

Wash hands thoroughly with soap and warm water after handling and before eating or smoking.

Ergonomic lifting techniques to be applied when lifting ammunition cartons.

Storage, including any incompatibilities:

Keep out of reach of any unauthorized personnel.

Keep out of reach of children.

Packaged ammunition should be stored in a cool dry environment in a common ammunition lockup (magazine).

Avoid striking the primer of an unchambered cartridge.

Ammunition should be disposed of as defective ammunition if any of the following conditions occur:

- Storage temperatures exceed 90°C (195°F).
- Evidence of corrosion.
- Physical damage.

SECTION 8.

Exposure Controls / Personal Protection (PPE)

Component		CAS #	OSHA PEL-TWA	ACGIH TLV-TWA	
CARTRIDGE CASE					
Aluminium Slide	Silicon	7440-21-3	15mg/m ³	10mg/m ³	
	Iron	7439-89-6	None Listed	No Limit Established	
	Copper	7440-50-8	0.1mg/m ³	0.2mg/m ³	
	Zinc	7440-66-6	None Listed	No Limit Established	
	Lead	7439-92-1	0.05mg/m ³	0.15mg/m ³	
	Bismuth	7440-69-9	None Listed	No Limit Established	
	Aluminium	7429-90-5	15mg/m ³	10mg/m ³	
	Magnesium	7439-95-4	None Listed	No Limit Established	
	Manganese	7439-96-5	5mg/m ³	0.2mg/m ³	
	Chromium	7440-47-3	1mg/m ³	0.5mg/m ³	
	Tin	7440-31-5	2mg/m ³	No Limit Established	
Titanium	7440-32-6	None Listed	No Limit Established		
Steel Body	Carbon	7440-44-0	15mg/m ³	2mg/m ³	
	Iron	7439-89-6	None Listed	No Limit Established	
	Lead	7439-92-1	0.05mg/m ³	0.15mg/m ³	
	Manganese	7439-96-5	5mg/m ³	5mg/m ³	
	Sulfur	7704-34-9	None Listed	No Limit Established	
	Silicon	7440-21-3	15mg/m ³	10mg/m ³	
Primer Cups	Phosphorous	7723-14-0	0.1mg/m ³	0.1mg/m ³	
	Copper	7440-50-8	0.1mg/m ³	0.2mg/m ³	
	Iron	7439-89-6	None Listed	No Limit Established	
	Lead	7439-92-1	0.05mg/m ³	0.15mg/m ³	
O Ring	Zinc	7440-66-6	None Listed	No Limit Established	
Striker Ball	Nitrile	Not Listed	None Listed	No Limit Established	
	Polyamide 66	32131-17-2	None Listed	No Limit Established	
Glass Fibre	Glass Fibre	65997-17-3	0	0	
	PROJECTILE				
Projectile Body	Silicon	7440-21-3	15mg/m ³	10mg/m ³	
	Iron	7439-89-6	None Listed	No Limit Established	
	Copper	7440-50-8	0.1mg/m ³	0.2mg/m ³	
	Zinc	7440-66-6	None Listed	No Limit Established	
	Lead	7439-92-1	0.05mg/m ³	0.15mg/m ³	
	Bismuth	7440-69-9	None Listed	No Limit Established	
Dome	Aluminium	7429-90-5	15mg/m ³	10mg/m ³	
	Polyamide 66	32131-17-2	None Listed	No Limit Established	
PRIMERS (FRONT)					
Primary Explosive	Lead Trinitroresorcinate	15245-44-0	0.05mg/m ³	0.15mg/m ³	
	Barium Nitrate	10022-31-8	0.5mg/m ³	No Limit Established	
	Antimony (III) Sulphide	1345-04-6	0.5mg/m ³	0.5mg/m ³	
	Tetrazene	109-27-3	None Listed	No Limit Established	
	Lead Dioxide	1309-60-0	0.05mg/m ³	0.05mg/m ³	
	Minium	1314-41-6	None Listed	No Limit Established	
Primers (Rear)	Penthrite	78-11-5	None Listed	No Limit Established	
	Primary Explosive	Lead Trinitroresorcinate	15245-44-0	0.05mg/m ³	0.15mg/m ³
		Barium Nitrate	10022-31-8	0.5mg/m ³	No Limit Established
		Tetrazene	109-27-3	None Listed	No Limit Established
		Lead Dioxide	1309-60-0	0.05mg/m ³	0.05mg/m ³
		Minium	1314-41-6	None Listed	No Limit Established
		Glass Powder	65997-17-3	15mg/m ³	15mg/m ³
		Styphnic Acid	82-71-3	None Listed	No Limit Established
		Nitrocellulose	9004-70-0	None Listed	No Limit Established
		Diphenylamine	122-39-4	None Listed	No Limit Established
		Centralite I	85-98-3	None Listed	No Limit Established
		2,4-Dinitroanisole	119-27-7	None Listed	No Limit Established
		Propellant	Nitrocellulose	9004-70-0	None Listed
Diphenylamine	122-39-4		None Listed	No Limit Established	
Centralite I	85-98-3		None Listed	No Limit Established	
Graphite Coating	7782-42-5		10mg/m ³	10mg/m ³	
2,4-Dinitroanisole	119-27-7	None Listed	No Limit Established		

Continued on page 7

Engineering Controls:

Normal handling of this product requires no special controls.
When Firing product local exhaust ventilation is recommended if significant dusting occurs or fumes are generated. Otherwise, use exhaust ventilation with explosion-proof ventilation.

Eye / Face Protection:

Normal handling of this product requires the use safety glasses.
When training with product always wear the appropriate PPE based on the type of training.

Hand Protection:

Not normally needed for handling this product.
When training with the UTM product always wear the appropriate PPE base on the type of training.

Skin Protection:

Not normally needed for handling this product.
When training with product always wear the appropriate PPE base on the type of training.

Respiratory Protection:

Not normally needed when handling this product.
If when firing the airborne concentrations exceed the above listed exposure limits wear respiratory protection in accordance with local regulations.

Hearing Protection:

When firing cartridges if noise levels exceed maximum regulatory levels it is advised that hearing protection is worn.

General Hygiene:

Do not eat, drink, or smoke while using this product.
When firing, avoid breathing fumes and smoke.
Wash hands thoroughly after use.

Safety Phrases:

For Hazardous Composition substances: S16, S22, S23, S29, S33, S35, S37, S39.

SECTION 9.

Physical & Chemical Properties

Appearance (colour, physical form, shape):

Cylindrical Cartridge - Aluminium (turned). Having a metallic projectile with a red plastic nose and two independent energetic compounds.

Property	Value	Property	Value
Odour:	None	Partition Coefficient: N-Octanol/water:	Not applicable
Odour Threshold:	Not applicable	Auto-Ignition Temperature:	Cartridges could spontaneously function (cook off) at 135 ° C (275 ° F)
Physical State:	Multi component assembly with water soluble marking paste	Decomposition Temperature:	Not Applicable
PH:	Not applicable	Heat Value:	Not applicable
Melting/ Freezing Point:	Not applicable	Particle Size:	Not applicable
Initial Boiling Point & Boiling Range:	Not applicable	Volatile Organic Compounds (VOC) Content:	Not applicable
Flash Point:	Cartridges could spontaneously function (cook off) at 135 ° C (275 ° F)	Softening Point:	Not applicable
Evaporation Rate:	Not applicable	Pour Point:	Not applicable
Flammability (solid, gas):	Not applicable	Viscosity:	Not applicable
Upper/Lower Flammability or Explosive Limits:	Not applicable	Bulk Density:	Not applicable
Vapour Density:	Not applicable	Percent Volatile:	Not applicable
Vapour Pressure:		Saturated Vapour Concentration:	Not applicable
Specific Gravity or relative Density:	Not applicable	Molecular Weight:	Not applicable
Solubility:	Insoluble	Molecular Formula:	Not applicable

SECTION 10.

Stability & Reactivity

Stability:

Product stable under normal use.

Normal operating temperature conditions between -5°C (40°F) and 40°C (104°F).

Conditions to Avoid:

Cartridge may function if the primer is inadvertently struck. Avoid subjecting to mechanical shock.

Product could spontaneously function if heated to 135°C (275°F).

Incompatible Materials:

Acids, Alkalis, Ammonia, Acetylene, Caustics Chlorine, Halogenated Hydrocarbons, corrosive or strong oxidizing substances.

Hazardous Decomposition Products:

Nitrogen Oxides, Carbon and Carbon Oxides.

Other dust and fumes may also be produced.

Possibility of Hazardous reactions:

No reported reactions.

SECTION 11.

Toxicological Information

Oral LD 50:

No Data.

Dermal LD 50:

No Data.

Inhalation LC 50:

No Data.

Risk Phrases:

For hazardous composition substances: R1, R3, R5, R6, R19, R21, R22, R36, R50, R67.

Sub Chronic/ Chronic Toxicity:

No Data

Carcinogenicity:

No Data

Mutagenicity:

This product is not known or reported to be mutagenic.

Reproductive, Teratogenicity, Or Developmental Effects:

This product is not known or reported to cause reproductive or developmental effects.

Neurological Effects:

This product is not known or reported to cause neurological effects.

Interactions With Other Chemicals Which Enhance Toxicity:

None known or reported.

SECTION 12.

Ecological Information

Eco-toxicity/ Persistence/ Degradability/ Mobility:

Data Known:

Nitrocellulose: LC50 > 1000 mg/l (fish, invertebrates, algae).

Bioaccumulation / Accumulation:

None known or reported.

Other Adverse Effects:

None known or reported.

SECTION 13.

Disposal Information

Disposal :

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements. This information presented below only applies to the material as supplied after firing. The identification based on characteristic (s) or listing may not apply if the material has not been fired or has been otherwise contaminated.

Damaged (Non-functioned) rounds:

Quarantined in classified packaging and disposed in accordance with local instructions for defective small arms ammunition.

Faulty (Non-functioned) ammunition:

Quarantined in classified packaging and disposed in accordance with local instructions for defective small arms ammunition.

Special precautions for landfill or incineration:

Damaged or defective ammunition may contain live explosive compound within the 'primers'.

Care should be taken when feeding the damaged or defective ammunition into an incinerator.

Personal Protective Equipment suitable to the burning work must be worn at all times.

(Note: Toxicity reports into spent cartridges have been carried out and may, subject to local regulations, be suitable for landfill disposal.

Copies of the reports are available on request.)

SECTION 14.

Transportation Information

Basic Shipping Information:

<u>Proper Shipping Name:</u>	Cartridges, Small Arms
<u>Hazard Class:</u>	1.4 S
<u>Subsidiary Hazard Class:</u>	Not Applicable
<u>Identification Number:</u>	UN0012
<u>Packing Group:</u>	Packaging Group II, Substances presenting medium danger. Packaging Group III, Substances presenting low danger.

Special Comments:

UTM Training ammunition is to be afforded the same handling and usage restriction as applied to common live ammunition.

Ammunition shipped domestically in the US can be reclassified as ORM-D or ORM-D Air (within guidelines). See 49 CFR 173.63 for ORM-D reclassification.

SECTION 15.

Regulatory Information

TSCA Inventory Status:

Components of this product are listed on the Toxic Substance Control Act inventory.

CERCLA:

Component	CAS #	RCRA Waste #	Final RQ Pounds (Kg)	
CARTRIDGE CASE				
Aluminium Slide	Silicon	7440-21-3	Not Listed	
	Iron	7439-89-6	Not Listed	
	Copper	7440-50-8	Not Listed	
	Zinc	7440-66-6	Not Listed	
	Lead	7439-92-1	Not Listed	
	Bismuth	7440-69-9	Not Listed	
	Aluminium	7429-90-5	Not Listed	
	Magnesium	7439-95-4	Not Listed	
	Manganese	7439-96-5	Not Listed	
	Chromium	7440-47-3	Not Listed	
	Tin	7440-31-5	Not Listed	
Steel Body	Titanium	7440-32-6	Not Listed	
	Carbon	7440-44-0	Not Listed	
	Iron	7439-89-6	Not Listed	
	Lead	7439-92-1	Not Listed	
	Manganese	7439-96-5	Not Listed	
	Sulfur	7704-34-9	Not Listed	
	Silicon	7440-21-3	Not Listed	
Primer Cups	Phosphorous	7723-14-0	Not Listed	
	Copper	7440-50-8	Not Listed	
	Iron	7439-89-6	Not Listed	
	Lead	7439-92-1	Not Listed	
O Ring	Zinc	7440-66-6	Not Listed	
	Nitrile	Not Listed	Not Listed	
Striker Ball	Polyamide 66	32131-17-2	Not Listed	
	Glass Fibre	65997-17-3	0	
PROJECTILE				
Projectile Body	Silicon	7440-21-3	Not Listed	
	Iron	7439-89-6	Not Listed	
	Copper	7440-50-8	Not Listed	
	Zinc	7440-66-6	Not Listed	
	Lead	7439-92-1	Not Listed	
	Bismuth	7440-69-9	Not Listed	
	Aluminium	7429-90-5	Not Listed	
Dome	Polyamide 66	32131-17-2	Not Listed	
PRIMERS (FRONT)				
Primary Explosive	Lead Trinitroresorcinat	15245-44-0	Not Listed	
	Barium Nitrate	10022-31-8	Not Listed	
	Antimony (III) Sulphide	1345-04-6	Not Listed	
	Tetrazene	109-27-3	Not Listed	
	Lead Dioxide	1309-60-0	Not Listed	
	Minium	1314-41-6	Not Listed	
PRIMERS (REAR)	Penthrite	78-11-5	Not Listed	
	Primary Explosive	Lead Trinitroresorcinat	15245-44-0	Not Listed
		Barium Nitrate	10022-31-8	Not Listed
		Tetrazene	109-27-3	Not Listed
		Lead Dioxide	1309-60-0	Not Listed
		Minium	1314-41-6	Not Listed
		Glass Powder	65997-17-3	Not Listed
		Styphnic Acid	82-71-3	Not Listed
		Nitrocellulose	9004-70-0	Not Listed
		Diphenylamine	122-39-4	Not Listed
		Centralite I	85-98-3	Not Listed
2,4-Dinitroanisole	119-27-7	Not Listed		
Propellant	Nitrocellulose	9004-70-0	Not Listed	
	Diphenylamine	122-39-4	Not Listed	
	Centralite I	85-98-3	Not Listed	
	Graphite Coating	7782-42-5	Not Listed	
	2,4-Dinitroanisole	119-27-7	Not Listed	

SARA 302:

None of the components in this product are listed.

SECTION 16.

Other Information

References:

- OSHA 29CFR 1910.
- ANSI Z400.1-2004.
- 49 C.F.R. 173.63.
- US Department of Health and Human Services, 11th Report on Carcinogens.
- State of California Environmental Protection Agency office of Environmental Health Hazard assessment safe Drinking Water and toxic enforcement Act 1986, chemicals known to the state to cause cancer or reproductive toxicity
- International Agency for Research on Cancer, Agents reviewed by the IARC Monographs, Volumes 1-100A, SEPTEMBER 11, 2009.
- US Environmental Protection Agency, EPA 550-B-01-003, List of Lists, Consolidated List of Chemicals Subject to the Emergency Planning and Community Right -To-Know Act (EPCRA) and Section 112(r) of the Clean Air Act.
- US Environmental Protection Agency, Substance Registry Services.
- NIOSH, National institute for Occupational Safety &Health, Pocket guide to chemicals hazards.
- ATSDR, Agency for Toxic Substances & Disease Registry, 2007 priority list.
- UN Recommendations on the Transport of Dangerous goods model regulations 14th edition
- Explosives (6th edition) by Rudolf Mayer.
- Chemicals Hazard Information and Packaging supply regulations (CHIP) approved supply list 7th edition
- U.K. competent authority documents.
- European Commission Joint Research Centre
- The physical and Theoretical Chemistry Laboratory, Oxford University

Prepared By:

UTM Ltd.

Additional Contact Info:

Additional information available from: www.utmworldwide.com

Notice:

The information in this MSDS should be provided to all who will use, handle, store, transport, or otherwise be exposed to this product. This information has been prepared for the guidance of plant engineering, operations and management and for persons working with or handling this product. UTM Ltd. believes this information to be reliable and current as of the date of publication, but makes no warranty that it is.

Disclaimer:

This information relates only to the specific product and its material and substances designated and may not be valid for such product and its material and substances used in combination with any other materials or in any process. This information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of this information for his own particular use.