



TECHNICAL DATA & USAGE SHEET

7.62x39mm BBR



Identifiers

Designation: 7.62x39mm BBR
 Origin: United Kingdom/United States
 P/N: 01-3093
 NSN (NATO): TBC
 Gross Package: Cardboard Carton containing 39 Boxes of 20 rounds.
 303mm (11.93in) x 184mm (7.24in) x 152mm (5.98in) (L x H x D)
 Gross Weight 5.2kg (11.5lb), NEQ 0.06kg (0.13lb)

Cartridge Components

Cartridge Case: Aluminium/Plastic
 Cartridge Assembly: 6g
 Cartridge Overall Length: 46mm / 1.81 in
 Front Primer: Boxer Primer
 Rear Primer: 6.3x9 Blank / Power Load
 Projectile: None

Ballistics

Average Muzzle Energy: Not Applicable.
 Average Muzzle Velocity: Not Applicable.
 Accuracy: Not Applicable.
 Maximum Effective Range for Training: Any distance that can be heard.
 Optimum Effective Range for Training: Any distance that can be heard.
 Standoff Distance: 0.5m / 18in

Operational Data

Noise Levels: Peak 150dB (Indoors).
 Operational Temperature Range: -32°C to 49°C (-26°F to 120°F)
 BFA: None Required (UTM RBT Conversion required).
 Compatible Weapon Types: 7.62x39mm SLR.

Storage

Shelf Life: Minimum six years in original packaging
 (Following recommended storage conditions).
 Recommended Storage: Dry environment, max storage
 temperature 40°C / 104°F

Warranty

18 months in original packaging (Following recommended storage
 conditions).



European Patent number: 1228342 additional patents pending. US patent numbers: 6253682, 6371028, 6427600, 6095051, 6378439, 6422149, 6415718, 6564719 UTM, Ultimate Training Munitions, and the "Breech" logo design are trademarks belonging to UTM Ltd.



TECHNICAL DATA & USAGE SHEET

7.62x39mm BBR

Purpose

- Provide a training round that emits a realistic noise and cycles the weapons with low emissions.
- Teach fundamentals of weapon handling, malfunction drills and marksmanship in any environment to include classroom.
- Essential building block between dry fire and live fire with introduction of noise and stress.
- Allow mission rehearsals/flow drills/scenarios in any environment.
- Use for SOP Development, refining Tactics, Techniques and Protocols, Skill Building, Scenarios and other collective level training.
- Compatible with certain virtual-reality interactive laser systems to add weapon recoil and weapon function realism.

Characteristics

- Normal weapon function and recoil.
- No Heat or Flame.
- No BFA required (UTM Conversion Kit required).
- 0.5m (18inch) stand-off allows safe and realistic training.
- Realistic and consistent cyclic rates in semiautomatic and automatic weapons, which match "Live" fire.
- Surpasses "Live Fire" reliability.
- Minimal environmental impact with low emission.

Available Alternatives (7.62x39mm BBR)

For more information on product alternatives and usage please contact UTM at:

sales@utmworldwide.com
+44 (0) 1638.711.003
+1.877.886.7233
+1.908.725.9000

Usage Guidelines

- UTM BBR converted weapons must be fired "clean and dry" in the weapon bore and barrel. NO LUBRICATION IN THE BARREL.
- Contact shots and shots to bare skin are prohibited. Maintain a 0.5m/18inch safe separation distance during training engagements.
- Appropriate hearing and eye protection (safety glasses or goggles) is mandatory.
- Intended only for supervised training conducted in accordance with UTM safety training protocols by military, law enforcement or professional training and security organizations.
- Keep all ammunition out of reach of children.
- UTM assumes no responsibility for injuries, loss or damage resulting from misuse of this or any of its products.
- Before using any UTM product, the end user must consult, and comply with, as applicable, all laws, rules, regulations, local ordinances, health and safety regulations, and safety practices recognized as standard in the firearms industry and for related training. The end user of any UTM product is solely responsible for any and all compliance in this regard.



WARNINGS

When converting back to 'Duty' use, ensure that the chamber and bore have been cleaned, cleared of all debris, objects or projectiles and inspected before firing a live round. Failure to ensure that the barrel of the host weapon is free from obstruction could result in damage to the barrel and/or injury to the operator.