

UTM MSDS, 01-3096 Silent Blank Rounds  
Revision No. 2

Revision Date: April 2018  
Supersedes: January 2017

This SDS has been prepared to GHS formatting, but is not a mandated SDS and provided for information purposes only.

### SECTION 1.

#### Product and Company Identification

<b>UK &amp; ROW Supplier:</b> UTM Ltd. Hampstead Avenue Mildenhall Suffolk IP28 7AS United Kingdom <a href="http://www.utmworldwide.com">www.utmworldwide.com</a>	<b>USA Supplier:</b> UTM Inc. 55 Readington Rd. North Branch, NJ 08876 USA	<b>Customer Service:</b> <u>United Kingdom &amp; ROW:</u> +44 (0) 1638 711 003 <u>Unites States Sales Office:</u> 1-877-866-7233 <u>United States Headquarters:</u> 908-725-9000
<b>Product Name:</b> Cartridges, Small Arms, Silent Blank Rounds. (Non – Lethal Training Ammunition). <b>Synonyms:</b> Silent Blank Rounds, SBR.  <b>Types:</b> 7.62x39mm.		
<b>Technical Support Service:</b> United Kingdom & Rest of World (ROW): <a href="mailto:sales@utmworldwide.com">sales@utmworldwide.com</a> Unites States: <a href="mailto:us.sales@utmworldwide.com">us.sales@utmworldwide.com</a> , <a href="mailto:us.military.sales@utmworldwide.com">us.military.sales@utmworldwide.com</a>		
<b>Emergency Phone Number:</b> <u>UK/ Rest of World (ROW):</u> +44 (0)1638 711 003 <u>USA:</u> 1-877-866-7233 or 908-725-9000		<b>Emergency Phone Hours:</b> <u>UK/ Rest of World (ROW) :</u> 9am to 5pm GMT <u>USA:</u> 9am to 5pm EST

### SECTION 2.

#### Hazards Identification

<b>Appearance / Odours:</b> An odourless metallic/plastic cylindrical cartridge.
<b>Emergency Overview:</b>  <p style="text-align: center;"><b>Warning!</b>  <b>Explosive, Keep away from heat.</b>  <b>Do not subject to mechanical shock.</b>  <b>Particles from firing may be harmful if inhaled.</b>  <b>Use (Training) without the appropriate Personal Protective equipment can cause bodily injury.</b>  <b>Do not take internally.</b></p>
Continued on page 2

## SECTION 2.

### Hazards Identification (continued)

**Specific Physical Hazards Arising From Product:**

Packaged and Loose cartridges could function (cook-off) if exposed to an external heat source in excess of 260°C (500°F) and could produce low velocity fragments which could cause eye injury or superficial skin wounds.

**Caution:**

When UTM training ammunition is fired, small amounts of particles can be emitted as well as gases. Upon over exposure this can be slightly irritating to the eye and respiratory tract. Emitted particles and or gases may contain trace amounts of harmful substances.

**OSHA Regulatory Status:**

This product contains material (s) considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

This product contains potential carcinogens as listed by OSHA, IARC or NTP.

(Note: Potential carcinogens as listed by OSHA, IARC or NTP are contained within the spent cartridge case, and do not vent to atmosphere under normal firing or handling conditions.)

**United Nations Hazard Classification:**

Classification 1.4S

**United Nations Designation:**

UN0014

**Potential Health Effects:**

Notes: This product unused is composed of various components sealed inside a metallic/plastic cartridge. Normal handling of this product in this condition poses no threat of exposure from harmful materials.

It is unlikely that the concentration of particles one would be exposed to from normal firing of this product would be sufficient to cause any of the effects listed.

Lead: Ingestion of large amounts of Lead can cause abdominal pain, constipation, cramps, nausea and/or vomiting. Chronic exposure to Lead can cause kidney damage, anaemia, reproductive effects, developmental effects and permanent nervous system damage in humans including changes in cognitive function.

Barium Nitrate: Irritation to eyes, skin, upper respiratory system; skin burns; gastroenteritis; muscle spasm; slow pulse, extrasystoles; hypokalemia

Antimony (III) Sulphide: Harmful by inhalation and if swallowed. May be harmful in contact with the skin. Skin, eye and respiratory irritant. Chronic exposure may lead to kidney or liver damage.

Tetrazene: May be harmful if swallowed or inhaled. Skin and eye irritant.

Nitrocellulose: Inhalation may irritate your nose, throat, skin and eyes. Toxic gases, such as oxides of nitrogen, hydrogen cyanide and carbon monoxide, which may be produced during decomposition or combustion of nitrocellulose.

Diphenylamine: Irritation to eyes, skin, mucous membrane; eczema; tachycardia, hypertension; cough, sneezing; methemoglobinemia; increased blood pressure, heart rate; proteinuria, hematuria (blood in the urine), bladder injury; In Animals: teratogenic effects.

Diethylether: Irritation to eyes, skin, upper respiratory system; dizziness, drowsiness, headache, excited, narcosis; nausea, vomiting.

**Medical Conditions Aggravated by Exposure:**

There are no medical conditions known to be aggravated by exposure to this product in its solid un-fired form. Exposure to Lead can aggravate Anemia, Cardiovascular and Respiratory Disease.

**Potential Environmental Effects:**

No Data.

Lead has been shown to be toxic to aquatic species.

### SECTION 3.

#### Components.

Product may contain the components listed below.

Component	Percentage by weight of cartridge	CAS #	
<b>CARTRIDGE CASE</b>			
Aluminium Body & Slide	Silicon	1.2%	7440-21-3
	Iron	<1.0%	7439-89-6
	Copper	3.8%	7440-50-8
	Zinc	1.6%	7440-66-6
	Lead	<0.3%	7439-92-1
	Bismuth	<1.0%	7440-69-9
	Aluminium	60.9%	7429-90-5
	Magnesium	1.4%	7439-95-4
	Manganese	<1.0%	7439-96-5
	Chromium	<0.4%	7440-47-3
	Tin	<0.1%	7440-31-5
Primer Cups	Titanium	<0.2%	7440-32-6
	Copper	8.1%	7440-50-8
	Iron	<0.1%	7439-89-6
	Lead	<0.1%	7439-92-1
O Ring	Zinc	4.3%	7440-66-6
	Nitrile	<0.5%	Not Listed
Slide Tip	Polyamide 66	19.5%	32131-17-2
	Glass Fibre	7.8%	65997-17-3
<b>PRIMERS (REAR)</b>			
Primary Explosive	Lead Trinitroresorcinate	<0.5%	15245-44-0
	Barium Nitrate	<0.4%	10022-31-8
	Antimony (III) Sulphide	<0.1%	1345-04-6
	Tetrazene	<0.1%	109-27-3
	Lead Dioxide	<0.1%	1309-60-0
Propellant	Nitrocellulose	<0.2%	9004-70-0
	Diphenylamine	<0.1%	122-39-4
	Diethylether	<0.1%	60-29-7
	Centralite I	<0.1%	85-98-3

Percentage of non reduced hazard substance as a percentage of the weight of the finished assembled round is 1-2% but this material is contained within the case of the spent cartridge.

## SECTION 4.

### First Aid Measures

**\* Eye Contact:**

Immediately flush out fume or particles with large amounts of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If eye irritation develops, call a physician immediately.

**\*Skin Contact:**

Wash skin with plenty of soap and water.

**\*Inhalation:**

If symptoms of lung irritation occur (coughing, wheezing or breathing difficulty), remove from exposure area to fresh air immediately. If breathing has stopped, perform artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.

**Ingestion:**

If ingested, immediately call a physician.

Items marked with an asterisk (\*) are conditions associated with the firing or discharge of the product and under normal conditions of transportation and handling of the product would not be a risk.

## SECTION 5.

### Fire Fighting Measures

**Flammable Properties:**

May detonate if heated to 260°C (500°F).

**Suitable Extinguishing Media:**

Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used.

Cool the containing vessel with a water jet in order to prevent the ammunition from functioning (cook-off).

Use water to cool ordinary surrounding combustibles.

Use flooding quantities of water.

Use wide fog pattern nozzle to stop any low velocity fragments.

**Specific Hazards Arising From Product:**

Packaged and Loose cartridges could function (cook-off) due to direct exposure to an external heat source and could produce low velocity metallic fragments which could cause eye injury or superficial skin wounds.

**Protective Equipment & Precautions for Fire-fighters:**

Wear full fire-fighter protective equipment including face shield or SCBA.

Minimum recommended distance for rescue personnel 10 meters (11 yards).

Evacuate the area to a radius of 100 meters (110 yards).

## SECTION 6.

### Accidental Release Measures

**Methods for Containment:**

Spills of this material should be handled carefully. Do not subject materials to mechanical shock. A spill of this material will normally not require emergency response team capabilities.

**Methods for Clean-up:**

If ammunition packing case should rupture, any loose cartridges should be placed into UTM classified packaging and the lid carefully secured.

Damaged/ Defective Ammunition should be quarantined into UTM classified packaging and disposed of in accordance with local instructions for defective ammunition, such as burnt in a standard ammunition incinerator.

## SECTION 7.

### Handling & Storage

**Handling:**

Keep out of reach of any unauthorized personnel.

Keep out of reach of children.

Wash hands thoroughly with soap and warm water after handling and before eating or smoking.

Ergonomic lifting techniques to be applied when lifting ammunition cartons.

**Storage, including any incompatibilities:**

Keep out of reach of any unauthorized personnel.

Keep out of reach of children.

Packaged ammunition should be stored in a cool dry environment in a common ammunition lockup (magazine).

Avoid striking the primer of an unchambered cartridge.

Ammunition should be disposed of as defective ammunition if any of the following conditions occur:

- Storage temperatures exceed 90°C (195°F).
- Evidence of corrosion.
- Physical damage.

**SECTION 8.**

**Exposure Controls / Personal Protection (PPE)**

Component	CAS #	OSHA PEL-TWA	ACGIH TLV-TWA	
<b>CARTRIDGE CASE</b>				
Aluminium Body & Slide	Silicon	7440-21-3	15mg/m <sup>3</sup>	10mg/m <sup>3</sup>
	Iron	7439-89-6	None Listed	No Limit Established
	Copper	7440-50-8	0.1mg/m <sup>3</sup>	0.2mg/m <sup>3</sup>
	Zinc	7440-66-6	None Listed	No Limit Established
	Lead	7439-92-1	0.05mg/m <sup>3</sup>	0.15mg/m <sup>3</sup>
	Bismuth	7440-69-9	None Listed	No Limit Established
	Aluminium	7429-90-5	15mg/m <sup>3</sup>	10mg/m <sup>3</sup>
	Magnesium	7439-95-4	None Listed	No Limit Established
	Manganese	7439-96-5	5mg/m <sup>3</sup>	0.2mg/m <sup>3</sup>
	Chromium	7440-47-3	1mg/m <sup>3</sup>	0.5mg/m <sup>3</sup>
	Tin	7440-31-5	2mg/m <sup>3</sup>	No Limit Established
	Titanium	7440-32-6	None Listed	No Limit Established
Primer Cups	Copper	7440-50-8	0.1mg/m <sup>3</sup>	0.2mg/m <sup>3</sup>
	Iron	7439-89-6	None Listed	No Limit Established
	Lead	7439-92-1	0.05mg/m <sup>3</sup>	0.15mg/m <sup>3</sup>
	Zinc	7440-66-6	None Listed	No Limit Established
O Ring	Nitrile	Not Listed	None Listed	No Limit Established
Slide Tip	Polyamide 66	32131-17-2	None Listed	No Limit Established
	Glass Fibre	65997-17-3	0	0
<b>PRIMERS (REAR)</b>				
Primary Explosive	Lead Trinitroresorcinate	15245-44-0	0.05mg/m <sup>3</sup>	0.15mg/m <sup>3</sup>
	Barium Nitrate	10022-31-8	0.5mg/m <sup>3</sup>	No Limit Established
	Antimony (III) Sulphide	1345-04-6	0.5mg/m <sup>3</sup>	0.5mg/m <sup>3</sup>
	Tetrazene	109-27-3	None Listed	No Limit Established
	Lead Dioxide	1309-60-0	0.05mg/m <sup>3</sup>	0.05mg/m <sup>3</sup>
Propellant	Nitrocellulose	9004-70-0	None Listed	No Limit Established
	Diphenylamine	122-39-4	None Listed	No Limit Established
	Diethylether	60-29-7	1200mg/m <sup>3</sup>	1500mg/m <sup>3</sup>
	Centralite I	85-98-3	None Listed	No Limit Established

Continued on page 7

**Engineering Controls:**

Normal handling of this product requires no special controls.  
When Firing product local exhaust ventilation is recommended if significant dusting occurs or fumes are generated. Otherwise, use exhaust ventilation with explosion-proof ventilation.

**Eye / Face Protection:**

Normal handling of this product requires the use safety glasses.  
When training with product always wear the appropriate PPE based on the type of training.  
Always wear UTM Face Mask and UTM approved Goggles when engaging in Force-on-Force training.

**Hand Protection:**

Not normally needed for handling this product.  
When training with the UTM product always wear the appropriate PPE base on the type of training.  
Always wear UTM Protective Gloves when engaging in Force-on-Force training.

**Skin Protection:**

Not normally needed for handling this product.  
When training with product always wear the appropriate PPE base on the type of training.  
Always wear a minimum of two layers of loose fitting clothing with no exposed skin when engaging in Force-on-Force training.

**Respiratory Protection:**

Not normally needed when handling this product.  
If when firing the airborne concentrations exceed the above listed exposure limits wear respiratory protection in accordance with local regulations.

**Hearing Protection:**

When firing cartridges if noise levels exceed maximum regulatory levels it is advised that hearing protection is worn.

**General Hygiene:**

Do not eat, drink, or smoke while using this product.  
When firing, avoid breathing fumes and smoke.  
Wash hands thoroughly after use.

**Safety Phrases:**

For Hazardous Composition substances: S16, S22, S23, S29, S33, S35, S37, S39.

## SECTION 9.

### Physical & Chemical Properties

**Appearance (colour, physical form, shape):**

Cylindrical Cartridge - Aluminium (turned) with a white plastic tip.

Property	Value	Property	Value
<b>Odour:</b>	None	<b>Partition Coefficient: N-Octanol/water:</b>	Not applicable
<b>Odour Threshold:</b>	Not applicable	<b>Auto-Ignition Temperature:</b>	Cartridges could spontaneously function (cook off) at 260 ° C (500 ° F)
<b>Physical State:</b>	Multi component assembly with water soluble marking paste	<b>Decomposition Temperature:</b>	Not Applicable
<b>PH:</b>	Not applicable	<b>Heat Value:</b>	Not applicable
<b>Melting/ Freezing Point:</b>	Not applicable	<b>Particle Size:</b>	Not applicable
<b>Initial Boiling Point &amp; Boiling Range:</b>	Not applicable	<b>Volatile Organic Compounds (VOC) Content:</b>	Not applicable
<b>Flash Point:</b>	Cartridges could spontaneously function (cook off) at 260 ° C (500 ° F)	<b>Softening Point:</b>	Not applicable
<b>Evaporation Rate:</b>	Not applicable	<b>Pour Point:</b>	Not applicable
<b>Flammability (solid, gas):</b>	Not applicable	<b>Viscosity:</b>	Not applicable
<b>Upper/Lower Flammability or Explosive Limits:</b>	Not applicable	<b>Bulk Density:</b>	Not applicable
<b>Vapour Density:</b>	Not applicable	<b>Percent Volatile:</b>	Not applicable
<b>Vapour Pressure:</b>		<b>Saturated Vapour Concentration:</b>	Not applicable
<b>Specific Gravity or relative Density:</b>	Not applicable	<b>Molecular Weight:</b>	Not applicable
<b>Solubility:</b>	Insoluble	<b>Molecular Formula:</b>	Not applicable



## SECTION 10.

### Stability & Reactivity

**Stability:**

Product stable under normal use.

Normal operating temperature conditions between -5°C (40°F) and 40°C (104°F).

**Conditions to Avoid:**

Cartridge may function if the primer is inadvertently struck. Avoid subjecting to mechanical shock.

Product could spontaneously function if heated to 260°C (500°F).

**Incompatible Materials:**

Acids, Alkalis, Ammonia, Acetylene, Caustics Chlorine, Halogenated Hydrocarbons, corrosive or strong oxidizing substances.

**Hazardous Decomposition Products:**

Nitrogen Oxides, Carbon and Carbon Oxides.

Other dust and fumes may also be produced.

**Possibility of Hazardous reactions:**

No reported reactions.

## SECTION 11.

### Toxicological Information

**Oral LD 50:**

No Data.

**Dermal LD 50:**

No Data.

**Inhalation LC 50:**

No Data.

**Risk Phrases:**

For hazardous composition substances: R1, R3, R5, R6, R19, R21, R22, R36, R50, R67.

**Sub Chronic/ Chronic Toxicity:**

No Data

**Carcinogenicity:**

No Data

**Mutagenicity:**

This product is not known or reported to be mutagenic.

**Reproductive, Teratogenicity, Or Developmental Effects:**

This product is not known or reported to cause reproductive or developmental effects.

**Neurological Effects:**

This product is not known or reported to cause neurological effects.

**Interactions With Other Chemicals Which Enhance Toxicity:**

None known or reported.

## SECTION 12.

### Ecological Information

**Eco-toxicity/ Persistence/ Degradability/ Mobility:**

Data Known:

Nitrocellulose: LC50 > 1000 mg/l (fish, invertebrates, algae).

**Bioaccumulation / Accumulation:**

None known or reported.

**Other Adverse Effects:**

None known or reported.

## SECTION 13.

### Disposal Information

**Disposal :**

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements. This information presented below only applies to the material as supplied after firing. The identification based on characteristic (s) or listing may not apply if the material has not been fired or has been otherwise contaminated.

Damaged (Non-functioned) rounds:

Quarantined in classified packaging and disposed in accordance with local instructions for defective small arms ammunition.

Faulty (Non-functioned) ammunition:

Quarantined in classified packaging and disposed in accordance with local instructions for defective small arms ammunition.

Special precautions for landfill or incineration:

Damaged or defective ammunition may contain live explosive compound within the 'primers'.

Care should be taken when feeding the damaged or defective ammunition into an incinerator.

Personal Protective Equipment suitable to the burning work must be worn at all times.

(Note: Toxicity reports into spent cartridges have been carried out and may, subject to local regulations, be suitable for landfill disposal.

Copies of the reports are available on request.)

## SECTION 14.

### Transportation Information

**Basic Shipping Information:**

<u>Proper Shipping Name:</u>	Cartridges, Small Arms
<u>Hazard Class:</u>	1.4 S
<u>Subsidiary Hazard Class:</u>	Not Applicable
<u>Identification Number:</u>	UN0014
<u>Packing Group:</u>	Packaging Group II, Substances presenting medium danger. Packaging Group III, Substances presenting low danger.

**Special Comments:**

UTM Training ammunition is to be afforded the same handling and usage restriction as applied to common live ammunition.

Ammunition shipped domestically in the US can be reclassified as ORM-D or ORM-D Air (within guidelines). See 49 CFR 173.63 for ORM-D reclassification.

**SECTION 15.**

**Regulatory Information**

**TSCA Inventory Status:**

Components of this product are listed on the Toxic Substance Control Act inventory.

**CERCLA:**

Component		CAS #	RCRA Waste #	Final RQ Pounds (Kg)
<b>CARTRIDGE CASE</b>				
Aluminium Body & Slide	Silicon	7440-21-3	Not Listed	Not Listed
	Iron	7439-89-6	Not Listed	Not Listed
	Copper	7440-50-8	Not Listed	5000 (2270)
	Zinc	7440-66-6	Not Listed	1000 (454)
	Lead	7439-92-1	Not Listed	10 (4.54)
	Bismuth	7440-69-9	Not Listed	Not Listed
	Aluminium	7429-90-5	Not Listed	Not Listed
	Magnesium	7439-95-4	Not Listed	Not Listed
	Manganese	7439-96-5	Not Listed	Not Listed
	Chromium	7440-47-3	Not Listed	5000 (2270)
	Tin	7440-31-5	Not Listed	Not Listed
Primer Cups	Titanium	7440-32-6	Not Listed	Not Listed
	Copper	7440-50-8	Not Listed	5000 (2270)
	Iron	7439-89-6	Not Listed	Not Listed
	Lead	7439-92-1	Not Listed	10 (4.54)
	Zinc	7440-66-6	Not Listed	1000 (454)
O Ring	Nitrile	Not Listed	Not Listed	Not Listed
Slide Tip	Polyamide 66	32131-17-2	Not Listed	Not Listed
	Glass Fibre	65997-17-3	0	0
<b>PRIMERS (REAR)</b>				
Primary Explosive	Lead Trinitroresorcinate	15245-44-0	Not Listed	Not Listed
	Barium Nitrate	10022-31-8	Not Listed	Not Listed
	Antimony (III) Sulphide	1345-04-6	Not Listed	5000 (2270)
	Tetrazene	109-27-3	Not Listed	Not Listed
	Lead Dioxide	1309-60-0	Not Listed	10 (4.54)
Propellant	Nitrocellulose	9004-70-0	Not Listed	Not Listed
	Diphenylamine	122-39-4	Not Listed	Not Listed
	Diethylether	60-29-7	U117	100 (45.4)
	Centralite I	85-98-3	Not Listed	Not Listed

**SARA 302:**

None of the components in this product are listed.

## SECTION 16.

### Other Information

**References:**

- OSHA 29CFR 1910.
- ANSI Z400.1-2004.
- 49 C.F.R. 173.63.
- US Department of Health and Human Services, 11th Report on Carcinogens.
- State of California Environmental Protection Agency office of Environmental Health Hazard assessment safe Drinking Water and toxic enforcement Act 1986, chemicals known to the state to cause cancer or reproductive toxicity
- International Agency for Research on Cancer, Agents reviewed by the IARC Monographs, Volumes 1-100A, SEPTEMBER 11, 2009.
- US Environmental Protection Agency, EPA 550-B-01-003, List of Lists, Consolidated List of Chemicals Subject to the Emergency Planning and Community Right -To-Know Act (EPCRA) and Section 112(r) of the Clean Air Act.
- US Environmental Protection Agency, Substance Registry Services.
- NIOSH, National institute for Occupational Safety &Health, Pocket guide to chemicals hazards.
- ATSDR, Agency for Toxic Substances & Disease Registry, 2007 priority list.
- UN Recommendations on the Transport of Dangerous goods model regulations 14th edition
- Explosives (6<sup>th</sup> edition) by Rudolf Mayer.
- Chemicals Hazard Information and Packaging supply regulations (CHIP) approved supply list 7th edition
- U.K. competent authority documents.
- European Commission Joint Research Centre
- The physical and Theoretical Chemistry Laboratory, Oxford University

**Prepared By:**

UTM Ltd.

**Additional Contact Info:**

Additional information available from: [www.utmworldwide.com](http://www.utmworldwide.com)

**Notice:**

The information in this MSDS should be provided to all who will use, handle, store, transport, or otherwise be exposed to this product. This information has been prepared for the guidance of plant engineering, operations and management and for persons working with or handling this product. UTM Ltd. believes this information to be reliable and current as of the date of publication, but makes no warranty that it is.

**Disclaimer:**

This information relates only to the specific product and its material and substances designated and may not be valid for such product and its material and substances used in combination with any other materials or in any process. This information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of this information for his own particular use.