



TECHNICAL DATA & USAGE SHEET

9mm UTX NMR



Identifiers

Designation: 9mm UTX

Origin: United Kingdom/United States

P/N: 01-3274

NSN (NATO): TBC

Gross Package: Cardboard Carton containing 20 Boxes of 50 rounds (in trays).

303mm (11.93in) x 184mm (7.24in) x 152mm (5.98in) (L x H x D)

Gross Weight 5.04kg (11.1lb), NEQ 0.04kg (0.09lb)

Cartridge Components

Cartridge Case: Aluminium

Cartridge Assembly: 4g

Cartridge Overall Length: 28mm / 1.10 in

Front Primer: Boxer Primer

Rear Primer: Boxer Primer

Projectile: See "Projectile Components" (Projectile is powered by primer only).

Ballistics

Average Muzzle Energy: Avg 2.8 Joules / 2.1ft/lbs

Average Muzzle Velocity: Avg 113m/sec (370fps)

Accuracy: 75mm (3.0in) at 7.5m/8.2yds (mean radius)

Maximum Effective Range for Training: Approximately 25m / 27yds

Optimum Effective Range for Training: Approx. 7.5m / 8.2yds & closer.

Standoff Distance: 0.25m / 10in - No Contact Shots.

Operational Data

Noise Levels: Peak 121dB (Indoors)

Operational Temperature Range: -10°C to 42°C (14°F to 108°F)

Storage

Shelf Life: Minimum six years in original packaging
(Following recommended storage conditions).

Recommended Storage: Dry environment, max storage
temperature 40°C / 104°F

Warranty

18 months in original packaging (Following recommended storage
conditions).



Projectile Components

Projectile Mass: 0.44g / 6.8gr

Projectile Assembly: A Plastic Base Cup which holds an Inertia ball and plastic cruciform dome.

European Patent number: 1228342 additional patents pending. US patent numbers: 6253682, 6371028, 6427600, 6095051, 6378439, 6422149, 6415718, 6564719 UTM, Ultimate Training Munitions, and the "Breach" logo design are trademarks belonging to UTM Ltd.



TECHNICAL DATA & USAGE SHEET

9mm UTX NMR

Purpose

- Accurate and reliable marking projectile for Force-on-Force or Force-on-Target training.
- Adds realism and stress to training by providing a threat of consequence with physical and visual stimulus.
- Use of Force/ROE, Tactics, Skill Building, Scenarios, Movement Drills and other Interactive Training.
- Use as a safe prelude or alternative to 'Live-Fire' target or CQB training.
- Accuracy and reliability allows for multiple firearms, CQB, and marksmanship applications (360° firing, movement drills, weapon transitions)

Available Alternatives (UTX NMR)

- Marking Projectiles

Usage Guidelines

- Whenever handling Converted Weapons during FOF training, UTM recommended and approved goggles, face mask, helmet and protective gloves are mandatory - no exposed skin.
- Converted weapons must be fired "clean and dry" in the weapon bore and barrel. NO LUBRICATION IN THE BARREL.
- UTM strongly recommends that at least two layers of loose fitting clothing or UTM PPE clothing be worn during "Force-on-Force" Training exercises using UTM ammunition. One layer of clothing (i.e. Military BDU/ACU) is mandatory.
- Contact shots and shots to bare skin are prohibited. Maintain a 0.25m/10in safe separation distance during training engagements.
- Appropriate eye protection (safety glasses or goggles) is mandatory.
- Intended only for supervised training conducted in accordance with safety training protocols by military or professional training and security organizations.
- Keep all ammunition out of reach of children.
- UTM assumes no responsibility for injuries, loss or damage resulting from misuse of this or any of its products.
- Before using any UTM product, the end user must consult, and comply with, as applicable, all laws, rules, regulations, local ordinances, health and safety regulations, and safety practices recognized as standard in the firearms industry and for related training. The end user of any UTM product is solely responsible for any and all compliance in this regard.

WARNINGS

When converting back to 'Duty' use, ensure that the chamber and bore have been cleaned, cleared of all debris, objects or projectiles and inspected before firing a live round. Failure to ensure that the barrel of the host weapon is free from obstruction could result in damage to the barrel and/or injury to the operator.

Disclaimer: Information contained in this publication is provided only for your convenience and is subject to change without notice. UTM MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION, INCLUDING BUT NOT LIMITED TO ITS CONDITION, QUALITY, PERFORMANCE, MERCHANTABILITY OR FITNESS FOR PURPOSE. UTM disclaims all liability arising from this information and its use. Use of UTM's products is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless UTM from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any UTM intellectual property rights.

Characteristics

- Normal weapon function and recoil.
- Non-Marking projectiles
- Realistic and consistent cyclic rates in semiautomatic and automatic weapons, which match "Live" fire.
- Surpasses "Live Fire" reliability.
- Minimal environmental impact - low emission and available in non-toxic options only.

Contact

For more information on product
alternatives and usage please
contact UTM at:

sales@utmworldwide.com
+44 (0) 1638.711.003
+1.877.886.7233
+1.908.725.9000